ΜΙΥΟΤΑ

MOVEMENT SPECIFICATIONS <u>CAL. 1L/M15 SERIES ANALOG QUARTZ MOV'T</u> BY CITIZEN WATCH CO., LTD. JAPAN <u>NEW FLAT RANGE</u> MANUFACTURED IN JAPAN

1.BASIC SPECIFICATION

(1) CAL. NO.

*TO CONFIRM WITH MOV'T DRAWING ATTACHED

•		
CALIBRE	1L15	1M15
Ligne Size*mm	6 x 8 18.1 x 16.1 x 17.8	10-1/2 23.3 x 22.6 x 22.6
Total height	2.71mm	2.71mm
Hands	2	
Date	0	0
Day of Week	X	X
Battery life	3 Year	
Battery	SR621SW or equivalent	

(2) Time standard

Type of quartz : Tuning fork type quartz crystalFrequency: 32,768HzAccuracy: +/-20 s/month worn under normal circumstances

(3) Battery installed

Type of battery : See above: JAPAN-MADE

(4) Others

Driving systems : Two-pole stepping motor Number of Jewel : No(0) jewel

(5) Additional Mechanisms & Features:

Quick Date Change by turning crown Powercell Saving Reset Mechanism(PSRM) Over-loading Compensation Device(OLCD) Digital Frequency Control(DFC) for time adjustment

(6) Balanceable weight of hand Minute hand Max. 0.4 N⋅m Setting stem Length of movement center to stem end... Thread..... 065-505 20.03mm Φ0.9 x 11.68mm

3. Others

* Measurement of time rate

The unit(gate) time of measurement must be set at "10 sec." or integer fold value of 10 sec. owing to the DFC system, and the measurement must be performed in the form of complete watch.

* Marking on movement

NO(0) JEWEL (CAL. NO.) MIYOTA CO., JAPAN

* Typical clearance

Mov't - Caseback	minimum 150 µm or more
Top of hands - Glass	300 - 400 µm *
* depending and subject to the glass and	d case structure, and hand length

* Interchangeability of appearance components:

Dial Foot positon & the diameter	same as Cal. 20/21/6L/6M series*
Date window position	same as Cal. 20/21/6L/6M series*
Hands	same as Cal. 2035/20/21/6L/6M series
*respectively plain to plain, date to date and d/d to dd	

*How to set time and date:


Date

----- Pull out crown to the first click position,

Time

turn crown counter-clockwise for Date

Pull out crown to the second click position and turn crown until the time is set correctly**



This specifications might be changed without prior notice.