


Cal. 2026

High Hand series of Cal.2025



1. Basic Specification

Calibre	2026
Ligne	6-3/4x8'''
Total height	3.15mm
Hands	2
Battery life	3

< Time Standard >

Type of quartz: Tuning fork type quartz crystal
 Frequency : 32,768Hz
 Accuracy : ± 20 second / month worn under normal circumstances

< Battery >

Type of battery: Silver oxide SR626SW or equivalent

< Others >

Driving system: Two-pole stepping motor
 Jewel : No jewels

< Additional Mechanisms >

Second hand stopping at optional position (2034,2035)
 Powercell saving reset mechanism
 Over-loading compensation device (2025,2035)

< Balanceable weight of hand >

Minute hand Max. 0.4 μ N.m
 Second hand Max. 0.07 μ N.m

2. Separated Parts

Calibre	2026
Setting stem	065-468
Hour Wheel	075-193
Dial washer	078-040

3. Remarks

< Setting stem >

Length of movement center to stem end : 20.0mm
 Thread : $\Phi 0.9$ mm x 12.38mm

< Measurement of time >

The unit time of measurement must be set at "10s" or integer fold value of 10s owing to the DFC system. And the measurement must be carried out in state of a complete watch.

< Marking on movement >

NO (0) JEWELS
 MIYOTA CO., JAPAN

< Typical clearance >

Between case and movement
 Battery strap - Case back : 150 - 300 μ m
 Hands - glass : 300 - 450 μ m*

* Depending and subject to the glass and case structure, and hand length.

These specifications might be changed without prior notice.