

RONDA slimtech 1000

Extra small and slim movements
for exclusive styles

Caliber 1042 – 4¼'''



Product Specifications

Analog quartz movement

Line

slimtech

Caliber

1042

Size

4¼'''

Version Swiss Made
Swiss Parts

5 Jewels / gold plated
5 Jewels / nickel plated

Battery life

36 Months

Hand fitting height

1

Features

– Metal movement, repairable

Functions

– 2 hands

Technical Specifications

Diameter Total	10.40 mm
Case fitting	10.00 mm
Movement height	2.90 mm
Height over Battery	2.90 mm
Movement rest	0.30 mm
Height over stem	0.55 mm
Length of stem travel	0.33 mm
Stem thread	0.70 mm
Battery type	335
Battery voltage	1.5 V
Battery life	36 Months
Current consumption – typical	0.23 µA
Current consumption – maximum	0.3 µA
Useful torque minute – typical	14 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Watch production

Drawing Casing ring (standard, PDF)
 Drawing Casing ring (standard, PDF)
 Drawing Dial (stem 3h, PDF)
 Drawing Hand fitting (hand height 0-1, PDF)
 Drawing Stem
 Movement holders for T2 (PDF)

Watch repairs

Technical instruction (PDF)