



RONDA startech 3500

Chronographs,
eye positions 6-9-12 and 6-12

Caliber 3520.D – 10½ x 11½'''



Product Specifications

Analog quartz movement

Line

startech

Caliber

3520.D

Size

10½ x 11½'''

Version Swiss Made
Swiss Parts

4 Jewels / gold plated
4 Jewels / nickel plated

Battery life

54 Months

Hand fitting height

1

Features

- Metal movement, repairable
- Very long battery life
- Power saving mechanism with pulled out stem: Reduction of consumption approximately 70%
- Very easy handling by two pushers

Functions

- 2 eyes
- Chronograph
- Center stop second (1/1 sec)
- 30 minute / 12 hour counter
- ADD and SPLIT functions
- Date
- Small second

Technical Specifications

Diameter Total	26.20 mm
Case fitting	23.90 mm
Movement height	4.90 mm
Height over Battery	4.90 mm
Movement rest	0.80 mm
Height over stem	1.70 mm
Length of stem travel	1.00 mm
Stem thread	0.90 mm
Battery type	384
Battery voltage	1.5 V
Battery life	54 Months
Current consumption – typical	1.14 µA (Date Mechanism not in Gear)
Current consumption – maximum	1.65 µA (Date Mechanism not in Gear)
Useful torque second – typical	6 µNm
Useful torque minute – typical	300 µNm
Useful torque center stop second – typical	6 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/+20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Watch production

[Drawing Casing ring \(standard, PDF\)](#)
[Drawing Dial \(stem 3h, calendar 3h, PDF\)](#)
[Drawing Hand fitting \(hand height 1, PDF\)](#)
[Drawing Stem](#)
[Casing information \(PDF\)](#)
[Movement holders for T2 \(PDF\)](#)

User's manual

[User's manual \(PDF\)](#)

