RONDA startech 5000

Chronographs, Big Date & Date, different calendar systems, Alarm

Caliber 5040.F – 12½'''





Product Specifications

Analog quartz movement	
Line	startech
Caliber	5040.F
Size	12½'''
Version Swiss Made	13 Jewels / gold plated
Battery life	54 Months
Hand fitting height	3

Features

- Metal movement, repairable
- Very long battery life
- Power saving mechanism with pullled out stem: Reduction of consumption approximately 70%
- Very easy handling by two pushers

Caliber 5040.F – 12½'''

Functions

- 3 eyes
- Chronograph
- Center stop second (1/1 sec)
- 1/10 seconds up to 30 minutes
- 30 minute counter
- 10 hour counter
- ADD and SPLIT functions
- Month indicator
- Day indicator
- Date by hand
- Small second

Technical Specifications

Diameter Total	28.60 mm
Case fitting	28.00 mm
Movement height	4.40 mm
Height over Battery	4.40 mm
Movement rest	0.60 mm
Height over stem	1.90 mm
Length of stem travel	0.90 mm
Stem thread	0.90 mm
Battery type	395
Battery voltage	1.5 V
Battery life	54 Months
Current consumption – typical	1.32 µA (Date Mechanism not in Gear)
Current consumption – maximum	1.65 µA (Date Mechanism not in Gear)
Useful torque second – typical	6 µNm
Useful torque minute – typical	300 µNm
Useful torque center stop second – typical	7 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Watch production

Drawing Casing ring (standard, PDF)
Drawing Dial (stem 3h, PDF)
Drawing Hand fitting (hand height 3, PDF)
Drawing Stem
Casing information (PDF)
Movement holders for T2 (PDF)

User's manual

User's manual (PDF)

Watch repairs

Technical instruction for code M (PDF)
Technical instruction up to code L (PDF)
Technical instruction as of code N (PDF)

RoHS 2005/95/EC